

MULTI PROCESS AC/DC WELDING MACHINE



SPARKLINE WELDERS

ISO 9001: 2015 Company

AC/DC PULSE TIG / MMA / CUT







Optional

Accessories





















- Tig torch 4m
- Earth clamp cable 300A earth clamp
- Welding cable with 300A electrode holder
- Gas hose 2mPlasma torch
- Air regulator

Model	Power Supply Voltage	Rate Input Capacity (KVA)	Rate Input Current (A)	No Load Voltage	Output Current Range	Duty Cycle	Weight L*W*H*(mm)	
DIGI-MULTI160ACDCPULS	1*230V, 50/60Hz	6.8	29	80	TIG:3-160A, MMA:5- 160A MMA:10-125A CUT:20-40A	60%	25 kg	560*240*460
DIGI-MULTI200ACDCPULS	1*230V, 50/60Hz	7.5	32.1	70	TIG:3-200A, MMA:5- 200A MMA:10-160A CUT:20-50A	60%	28 kg	560*240*460
DIGI-MULTI250ACDCPULS	1*230V, 50/60Hz	10	41	80	TIG:5-200A, MMA:10- 250A MMA:10-200A CUT:20-60A	60%	30 kg	560*240*460

In view of continuous Development, we reserve the rights to modify the design, specifications and or dimensions without notice.