



TIG WELDING MACHINE



**SPARKLINE
WELDERS**

ISO 9001 : 2008 Company



Optional Accessories



- Tig torch 4m
- Earth clamp cable 500A earth clamp
- Welding cable with 500A electrode holder
- Gas hose 2m

Model	Power Supply Voltage	Rate Input Capacity (KVA)	Rate Input Current (A)	No Load Voltage	Output Current Range	Duty Cycle	Weight L*W*H*(mm)
SUPERTIG 315	3*400V, 50/60Hz	11.5	16.6	70	TIG:10-315A, MMA:10-250A	60%	30 kg 560*240*460
SUPERTIG 400	3*400V, 50/60Hz	16.8	24.3	70	TIG:10-400A, MMA:10-315A	35%	31 kg 560*240*460
SUPERTIG 400D	3*400V, 50/60Hz	16.8	24.3	80	TIG:10-400A, MMA:10-315A	60%	38 kg 590*290*650
SUPERTIG 500D	3*400V, 50/60Hz	25	37	80	TIG:10-500A, MMA:20-400A	60%	46 kg 590*290*650
SUPERTIG 400DP	3*400V, 50/60Hz	16.8	24.3	80	TIG:10-400A, MMA:10-315A	60%	40 kg 590*290*650

In view of continuous Development, we reserve the rights to modify the design, specifications and or dimensions without notice.